

HAD系列自动排水器


Series Auto Drain

HAD402 系列自动排水器

series Auto Drain



外形尺寸 Outlook & Dimension



注意事项 Points for Attention

使用时，必须垂直位置安装，且使排水口朝下
When using, the drainer should be installed vertically the drain port facing down.

产品特点 Features

自动排水/Auto drainer 停气排水/Air Shut off Drain
手动排水/Manual Drain
水杯配有金属保护罩/The water cup is provided with metal protective cover

用途 Application

常用于自动排除管道低处、冷冻式空气干燥机、油水分离器、储气罐级各种空气过滤器底部等处的积水。可安装在不便于进行人工排放污水的地方，如高处低处、狭隘处；特别是安装在气量较大、放水次数较频繁的地方，可防止人工排水被遗忘而造成压缩空气被冷凝水重新污染。

This product applies to auto remove the seeper at the lower places of piping, frozen type air drying machine, Oil separator, air storage tanks and the bottom of various air filters. It can be installed in the places inconvenient for manual drain, such as higher, lower and narrow places, especially there's large consumption of frequent water drains. It can prevent the compressed air being re-polluted by condense water resulting from neglect of manual drain.

技术参数 Specification

型号/Model	HAD402-02	HAD402-02	HAD402-02
保证耐压力/Ensured Pressure Resistance	1.5MPa		
动作压力/Operating Pressure	0.15~1.00MPa		
环境及流体温度/Ambient and Fluid Temperature	5~60°C		
接管口径/Port Size	G1/4	G3/8	G1/2
排水口径/Drain Port Size	G1/8		
排水状态/Drain Status	常开型/Normal open		
工作介质/Working Medium	压缩空气/Compressed air		